

A full service provider of Pennsylvania Uniform Construction Code (UCC) services.

Uniform Construction Code

BUILDING, STRUCTURE AND FACILITY PERMIT

Lamar Township

LOCAL LIGHT-HEIGEL OFFICE CONTACT INFORMATION:

Light-Heigel & Associates, Inc. 135 Walter Drive Suite 3 Lewisburg PA 17837 *Attn: Building Codes* Phone: (717) 821-5381

FOR ADDITIONAL INFORMATION: E-mail:Kylek@light-heigel.com Website: www.light-heigel.com

Table of Contents

Building, Structure and Facility Permit: Application Requirements • 3

Application for Building Permit • 6

Commercial Fee Schedule • 9

UCC Plan Review Checklist • 12

Special Inspections and Observations Statement • 18

Energy Code Prescriptive Compliance Report • 22

BUILDING, STRUCTURE, AND FACILITY PERMIT: Application Requirements

The following items (1-9) constitute a complete UCC application package for the construction of:

• New buildings, structures and facilities, except:

* Modular or industrialized construction - please complete the MODULAR CONSTRUCTION BUILDING PERMIT application package * Shell buildings - please complete the BUILDING SHELL PERMIT application package.

- Additions to existing buildings.
- Alterations (renovations) that will exceed the scope of ALTERATIONS-LEVEL 1 (as defined in the International Existing Building Code) and that will be made to existing buildings that are legally occupied.
- 1. A completed UCC APPLICATION FOR BUILDING PERMIT.
 - Please complete this fully. If an informational item does not apply, indicate this with "NA."
 - It is imperative that applicants indicate the name of the **political subdivision** and the **county** where the proposed construction will occur. Without this, we cannot verify that Light-Heigel has jurisdiction for this work. We will not process applications that lack this information.

2. Payment in full of the amount(s) determined on the COMMERCIAL FEE SCHEDULE.

Fees paid cover plan review and all inspections.

3. Two (2) complete sets of construction drawings and one (1) set of specifications.

- Seals of licensed design professionals must appear on all sheets and be signed and dated by the designer. (An unlicensed person may prepare construction drawings for the **alteration** or **remodeling** of a building, if no compensation is paid for their preparation and the construction will not involve changes in the building's structure or means of egress.)
- Drawings must be at least 18" x 24" (but no more than 36" x 42") in size, drawn to scale of no less than 1/8"=1', with sufficient detail to fully indicate the nature and scope of the work to be performed.
- On the first page of each set, indicate any systems or installations for which plan submission is deferred (e.g., fire alarm system, pre-engineered truss system, sprinkler system).

Applicants/design professionals should note the following regarding deferred submittals:

- a. Plans for any deferred systems must be submitted as a plan revision at least 2 weeks before proposed installation.
- b. Per §403.43(k) of the UCC regulation, these plans must bear the signature of the design professional in responsible charge and a brief statement indicating that the design professional has reviewed the plans and found them to be in general conformance with the design of the building or structure.

- Provide a **building code summary** on the first or second sheet of the drawings, with all applicable building code sections filled out.
- 4. Two (2) copies of a site plan showing the size and location of the new construction, with accurate boundary lines, distances from lot lines, and the established street grades and proposed finish grades. (See also the UCC PLAN REVIEW CHECKLIST for additional requirements.)

5. If applicable, a copy of the SPECIAL INSPECTIONS AND OBSERVATIONS STATEMENT.

- This document must be completed and submitted in the application package whenever one or more of the special inspections or structural observations (detailed in sections 1704 and 1709 of the *International Building Code*) is required for the proposed work.
- This statement must be signed by the design professional in responsible charge of the project.

There are occasions when building owners or their representatives may not know who will be performing the special inspections required in Chapter 17, at the time they make application for a UCC building permit. When this occurs, applicants may submit, in lieu of a completed **SPECIAL INSPECTIONS AND OBSERVATIONS STATEMENT** form, a letter stating:

- Why the **SPECIAL INSPECTIONS AND OBSERVATIONS STATEMENT** cannot be submitted with the application for a building permit;
- The applicant understands that two (2) completed copies of the **SPECIAL INSPECTIONS AND OBSERVATIONS STATEMENT** will have to be submitted to our inspector at the time of the first required inspection; and,
- The applicant is aware that the first required inspection (typically, the footer inspection) will not occur, and that work may not continue, unless the completed copies of the **SPECIAL INSPECTIONS AND OBSERVATIONS STATEMENT** are available at the job site.

A Stop Work Order will be issued, should work continue after our inspector has visited the construction site and learned that the required documents are not available.

- 6. When construction will occur in a flood plain, one (1) copy of one of the certifications required in section 1612.5 of the *International Building Code*.
- 7. The following information indicating compliance with the *International Energy Conservation Code.*

Submit one (1) copy of the compliance certificate generated by the COMcheck EZ software. Be sure to utilize version 4.0 Release 1 (or higher) and to select the IECC as the code to which you will demonstrate compliance.

OR

Submit one (1) copy of the ENERGY CODE PRESCRIPTIVE COMPLIANCE REPORT with the face page and all applicable main component prescriptive reports completely filled out. **EXCEPTION:** If the building or structure is exempt per ASHRAE 90.1 2.3B, include a letter signed by the design professional in responsible charge that the building or structure will use neither electricity nor fossil fuels and is thus exempt from energy conservation code requirements.

Note: If the proposed construction involves a building or structure classified in use group R-2 and it is not more than three stories in height above grade, compliance should be demonstrated with the **residential** requirements of the *International Energy Conservation Code*. In this case, or if the building permit application is for a R-3 occupancy, supply three (3) copies of the compliance report generated by the REScheck software.

To obtain copies of the US DOE COMcheck EZ (use version 4.0 Release 1 or higher) or REScheck (use version 3.6 Release 1 or higher) software needed for determination of energy code compliance, visit the US DOE "Building Energy Codes Program" website (www.energycodes.gov).

8. If alternative construction methods or materials are proposed for use, a statement signed by the design professional, certifying that the proposed methods or materials meet the requirements of 34 PA Code §403.44.

9. A fully completed copy of the UCC PLAN REVIEW CHECKLIST.

Failure to include this or to fill out the list completely will delay review of your application and may be cause for return of the entire application package without review. If an item on the list does not apply, indicate this by placing "NA" on the check-off line.

Uniform Construction Code (UCC)
APPLICATION FOR BUILDING PERMIT

	ALLEIOAHON			
	Accessibility Only Review		Addition	
Application	Alteration or Renovation		New Building	
Туре	New Structure/Facility		Phased Approval	
	Plan Revision or Partial Oct	cupancy Reques	t 🛛 Unapproved Existing Building	
Use/Occupancy	□ A-1 □ A-2 □ A	-3 🗌 A-4	□ A-5 □ B □ E	
Classification: Check box to <u>left</u> of	□ F-1 □ F-2 □ H	-1 🗌 H-2	🗌 H-3 🛛 🗌 H-4 🗌 H-5	
applicable group. Check all that apply.	□ I-1 □ I-2 □ I-	3 🗌 I-4	□ M □ R-1 □ R-2	
Check all that apply.	🗌 R-3 Adult Care 🛛 🗌 R	-3 🗌 R-4	□ S-1 □ S-2 □ U	
Site Information	Project Name			
(Political Subdivision & <u>County</u> names are	Street Name and #			
required.)	City Political Subdivision	State	e Zip Code	
Createl				
Special Requirements &	Two (2) site plans		owing will be submitted with this application: vo (2) complete sets of construction drawings	
Documentation	One (1) completed copy of the	UCC PLAN REV	IEW CHECKLIST	
	One (1) set of specifications (only if <u>Addition</u> , <u>A</u>	<u> Alteration, New Building</u> or <u>New Structure/Fac</u>	;ility)
	Does this co nstruction involve	☐ Yes ☐ No	If "Yes," submit 1 copy of a letter from a license	ed
	modular units built in a factory?		design professional certifying that construction	
			within the modular units (or the fully assembled	
			modular building) and hidden from view will full comply with all requirements of the UCC.	y
	Is this construction regulated by	🗌 Yes 🗌 No	If "Yes," submit 1 copy of approval letter from	the
	the Health Care Facilities Act?		Pennsylvania Department of Health.	
	Is this construction exempt from energy code requirements?	🗌 Yes 🗌 No	If " Yes ," submit 1 copy of letter indicating that the building or structure will use neither electri	
	energy code requirements?		nor fossil fuels, and thus is exempt per ASHR	
			<i>90.1</i> , §2.3(B).	
			If "No," submit 1 copy of the COMcheck Certificate or the ENERGY CODE PRESCRIPT	
			COMPLIANCE REPORT.	
	Is project in flood hazard area?	🗌 Yes 🗌 No	If "Yes," submit 1 copy of one of the flood haz	
			certifications mandated in section 1612.5 of t	th e
	Are any of the International	🗌 Yes 🗌 No	International Building Code. If "Yes," submit 1 copy of the SPEC	
	Building Code (Chapter 17)		INSPECTIONS OBSERVATIONS STATEMEN	
	special inspection or structural			
	observations required? Will an alternative construction	Yes No	If " Vac " submit a signed statement indicating t	that
	method or material be used on		If " Yes ," submit a signed statement indicating the proposed method or material meets the	
	this project?		requirements of 34 PA Code §403.44.	
	Is this application for "phased approval"?	🗌 Yes 🗌 No	If " Yes ," submit a letter sign ed by the desi	
	approvar ?		professional and owner acknowledging that t issuance of a permit for pha sed construct	
			provides no assurance that the municipa lity	will
			grant approval of any UCC permits needed	
			complete the construction, and th at the des professional and owner will ensure that	
			building/structure fully complies with all U	
			requirements before occupancy.	

Project Data	Lot Number: Block Number:
	Does municipality have a zoning ordinance? □ Yes □ No If "Yes," has permit been acquired? □ Yes □ No If "Yes," has permit been acquired? □ Yes □ No
	Minimum setbacks required by municipal zoning ordinance (in feet): Front: Rear: Right Side: Left Side:
	Sq. ft. of conditioned space Sq. ft. of unconditioned space
	Number of stories above grade Does it have a basement? Total floor area (sq. ft.)
	Floor area new construction (sq. ft.)
	# of multi-family dwelling units # of accessible dwelling units
	Type(s) of construction per Chapter 6 of the <i>International Building Code</i> (check all that apply):
	Fire suppression: 🗌 Full 🔄 Partial 🗌 None
	If application applies to an existing building that is " legally occupied ", indicate permits held: Fire and Panic Occupancy Permit Municipal Occupancy Permit Municipality Name L&I UCC Certificate of Occupancy File number:
	If " legally occupied ," you must select which code requirements the building will comply with (choose only one):
	🗌 International Existing Building Code 👘 🗌 Chap. 34, International Building Code
	Cost of Construction: Tax Parcel ID #:
Design Professional In Responsible Charge Seal must be in space to right of name & address.	Name:
	Phone: Fax:

			Permit #: Date:	
Owner Information	Owner Name Street Address City Phone Number	State	Zip Code	e
Deferred Submissions	application, check th plan set.	ting plans and other docum e appropriate box below <u>an</u> n	<u>d</u> indicate this on the first	st page of each building
Fees: Refer to COM	MERCIAL FEE SCHE			
As the owner of 1. Th bu 2. Th vic 3. Th (in sp 4. Ar 5. If t no 6. W ex 7. No sh	the estimated construction inding permit is correct the building or structure plations are corrected a nis project will be constructure of the constructure of the day required not be cified in 34 PA Code my changes to the appre- the licensed architect of the licensed architect of the required, up to 200 tisting building will be endown or omission in endown of the constructure of error or omission in endown of the structure to the constructure of the constructure of the constructure of the constructure the required, up to 200 the performance of the constructure of the constructure of the constructure of the constructure of the constructure of the constructure	described in this applicatio and a Certificate of Occupan ructed in accordance with t on-design changes) and the Chapters 401-405. oved documents will be file or engineer in responsible c be provided to the municipa % of the total cost of any we expended to provide an accu- ither the drawings and spec- e from constructing the work	ation provided as part on m will not be occupied un ney has been received. The approved drawings a e Uniform Construction d with the municipal UC harge of this construction al UCC Building Code O ork performed on an are essible route to the area cifications or application	of this application for a ntil all known code and specifications Code standards as C Building Code Official. In should change, written official. In a of primary function in an of primary function. , whether approved or not,
Applicant Na Street Addres City	SS	State		de
	per			

Uniform Construction Code (UCC)

COMMERCIAL FEE SCHEDULE

for

Pennsylvania UCC Municipal Enforcement Program

SERVICE 1. New Construction and Additions - Base Fee	UNIT PRICE \$0.35/ SqFt
2. Remodeling (see definition below) - Base Fee	\$0.25/ SqFt
All Plan Reviews and Inspections required on the standard Commercial Sub are included in these permit fees.	omittal Sheet
Note: Special Inspections required by IBC are at Owners Expense.	
See Worksheet below to calculate Building Permit and Sub-category fe	ees.
3. Alterations or Repairs to electrical, gas, mechanical or plumbing installations	5.
a. Single Event Permit (one inspection only)	\$400.00
 b. Annual Permit (Inspections in each appropriate discipline are also required) 	\$400.00
 Follow-up Inspections for Incomplete or Compliance Inspections for Annual Permit or Single Event Permits requiring additional inspections (per trip) 	\$200.00
5. Meeting attendance/Hearing attendance	\$102.00
6. Next Day Mail Service	\$25.00
 Other services - Provided at No Charge to the Client: Telephone calls, correspondence, mileage, postage 	
DEFINITIONS:	

Remodeling is work that includes none of the following:

- (1) Change in Occupancy/Use Group.
- (2) Modify Structural or Firewalls.
- (3) Addition or upgrade of electrical, plumbing, or HVAC services.
- (4) Addition to structure of any kind.

Annual Permit – as allowed in the UCC regulation (403.42(f)). Applicant must regularly employ qualified tradespeople. Applicant must keep detailed records of all alterations made under the permit. Applicant will submit copies to the BCO on a predetermined time schedule. BCO will schedule appropriate inspections for modifications made in the previous timeframe. Applicant will be billed for each required Compliance Inspection(s) at the time of inspection.

Instructions for Completing the Permit Fee Worksheet

- 1. Insert **Proposed Total Building Area** in Position A of Worksheet.
 - a. If building is new, use Total Building Area.
 - b. If work is addition or remodel, use Total Construction Area.
 - c. Minimum is 3000 SqFt.
- 2. Choose Proper Usage Group Code Factor from the Chart below and insert in Position B of Worksheet.
 - a. If multiple Usage building, select Primary Usage.
- 3. Multiply the <u>Area</u> and <u>Usage Factor</u> with the <u>Base Fee</u> to obtain the Building Permit Fee amount for Position D.
- Calculate Permit Fees for Mechanical, Plumbing, Accessibility/Energy at 25% of the Building Permit Fee. The Electrical Permit is calculated at 30% of the Building Permit Fee. Insert the amounts in Positions E – H as necessary.

COMMERCIAL BUILDING PERMIT FEE WORKSHEET

Α.	Project or Building Area (Minimum 3000SqFt)						SqFt
В.	Usage Group Factor						X
C.	Base Fee						X \$
D.	Building Permit Fee (BPF)					\$	
E.	Mechanical Permit Fee	0.25 X	\$_	(BPF)	=	\$	
F.	Plumbing Permit Fee	0.25 X	\$	(BPF)	=	\$	
G.	Accessibility/Energy Permit F	⁻ ee 0.25 X	\$	(BPF)	=	\$	
H.	Electrical Permit Fee	0.30 X	\$	(BPF)	=	\$	
				State Fee	+	\$	4.50
тс	Check made payable to: LI	GHT-HEI			= INC	\$	
	FOR OFFICE USE CHECK #		RE	CEIVED ON		BY	
M	JNICIPAL FEE <u>= N</u> Make <u>additional</u> check made FOR OFFICE USE	e payable	to th	e Municipality: <i>Lar</i>	mar	\$ Township	
	CHECK #		RE	CEIVED ON		BY	

Usage Group Factors

Factor	Usage Group
2.0	12
1.6	A1
1.5	(A3-Churches), I3
1.2	A2, A4, (A3-nonchurch), A5
	B, E, H5, I1, I4, R1, R4
1.0	R2, R3
0.9	Μ
0.7	F1, F2, H1, H2, H3, H4, S1, S2
0.5	U

Usage Group definitions per Chapter 3 of current International Building Code.

A Assembly

- A-1 Theaters
- A-2 Restaurants
- A-3 Worship, recreation and amusement
- A-4 Indoor Sports
- A-5 Outdoor Sports
- **B** Business

E Education

F Factory

- F-1 Moderate Hazard
- F-2 Low Hazard

H High Hazard

- H-1 Detonation Hazard
- H-2 Deflagration or Accelerated burning
- H-3 Readily support combustion
- H-4 Health hazards
- H-5 Semiconductor fabrication

I Institutional

- I-1 Ambulatory
- I-2 Hospital
- I-3 Prison
- I-4 Day Care

M Mercantile

R Residential

- R-1 Hotel
- R-2 Apartment House
- R-3 One & Two Family
- R-4 Assisted Living

S Storage

- S-1 Moderate Hazard
- S-2 Low Hazard

U Utility & Misc

Uniform Construction Code (UCC) UCC PLAN REVIEW CHECKLIST

This checklist must accompany permit applications for new buildings/structures, additions and renovation projects (those which exceed the scope of ALTERATIONS-LEVEL 1)

ALL INFORMATION MUST BE FILLED IN, CHECKED OR MARKED "N/A"

Project Name:

Project Address:

Owner/Agent:	Telephone:
Design professional or other person we can contact about info on this form and	
other project details (if same as Owner/Agent, just provide fax # and e-mail	Telephone:
address):	
	Fax:
	E-mail:

General Requirements:

All drawings shall be sealed, signed, and d ated by a design professional (licensed arch itect or engineer). The only exception is when all of the following apply:

- a) The proposed work only involves remodeling or alterations of an existing building or structure.
- b) The proposed work does not change the building's structure or means of egress.
- c) The person preparing the plans is not compensated for the preparation of the drawings.

All drawings must be neatly drawn with clean, crisp lettering --- they must remain legible after reduction for microfilming.

Computer-generated vicinity maps obtained from web-based services (such as *MapQuest*) are acceptable, as long as the roadways or street names are legible <u>and</u> will remain that way after reduction for microfilming.

When photographs (including digital ones) are submitted to show building elevations, the images must be in focus and correctly exposed.

A Pennsylvania Department of Tra nsportation (PennDOT) permit allowing access to a highway under its jurisdiction is not required at the time t hat application is made for a UCC building permit. If the highway occupancy permit issued by PennDOT requires a location o f the building/structure differing from that approved under the UCC buildingpermit, applicants must send the municipal UCC BCO a letter requesting a determination whether a revision of approved plans will be required.

While we understand t hat many it ems on this checklist may not be included in some alteration or renovation projects, we request that all applicant s work through the entire checklist to ensure that any necessary items are included. If any item is <u>not necessary</u>, <u>please check N/A</u> ("not applicable"). This will greatly facilitate review and approval of projects.

If any of the non-mandatory sections (any sections other than Site Plans and Architectural Plans) in this document do not apply to the proposed work, please check the "N/A" box beside the section title (rather than fill in "N/A" next to each item in that section.

SITE PLANS:

🗌 Yes	□ N/A	a.	Site plans shall be prepared to scale (not less than 1"=20'), with legend, north arrow, and
🗌 Yes	□ N/A	b.	<u>separate</u> vicinity (site location) map. Show the correct street address, parcel number and required municipal zoning (if there is local zoning ordinance) on the site plans.
🗌 Yes	□ N/A	C.	
🗌 Yes	□ N/A	d.	Show all a ccessible parking spaces and sig nage per ICC/A NSI A117.1 and the <i>International Building Code</i> on site plan.
🗌 Yes	🗌 N/A	e.	Show accessible curb cuts, ramps and access ways to the building.
🗌 Yes	🗌 N/A	f.	Show all existing and proposed driveway entrances.
🗌 Yes	🗌 N/A	g.	Identify adjacent land uses and zoning.
🗌 Yes	🗌 N/A	ĥ.	Show all easements, flood ways, and required buffers.
Yes	N/A	i.	Show existing and proposed utilities (with backflow preventers) to serve the site.
🗌 Yes	🗌 N/A	j.	Show existing and proposed finish grades.
🗌 Yes	🗌 N/A	k.	Show details, sections, and elevations needed for construction.
🗌 Yes	N/A	I.	Show all buffer and screening landscaping.
🗌 Yes	🗌 N/A	m.	Show all required parking and loading spaces and calculations.

ARCHITECTURAL PLANS:

☐ Yes	□ N/A	a.	Show architectural floor plans of each floor. These pages must be at least $18" \times 24"$ in size (but not more than $36" \times 42"$), drawn to a scale of not less than $1/8" = 1'$. Indicate (or reproduce) the approved, tested hourly rating, number, and location of all rated members and assemblies (walls, columns, beams, floor and ceiling, and ceiling and roof fire-rated design assemblies).
🗌 Yes	🗌 N/A	b.	Show the square footage of each floor on the corresponding floor plans.
🗌 Yes	🗌 N/A	C.	Identify the names and uses of each room.
🗌 Yes	🗌 N/A	d.	Furnish door schedule(s), including size, type, rating (if any) and hardware.
🗌 Yes	🗌 N/A	e.	Provide all glazing schedules.
☐ Yes	□ N/A	f.	Show elevations with dimensions defining overall building height, floor-to-floor heights, or heights to ridge and eave as applicable to the type of building construction listed on the UCC application. (Note: Where an existing building is involved, photographs of all sides of the building may be submitted to show elevations. These will be acceptable only if they show all elements necessary to determine compliance with the UCC.)
🗌 Yes	🗌 N/A	g.	Provide basement percentage-below-grade calculations.
🗍 Yes	🗍 N/A	h.	Indicate roof slopes, drainage system and sized through wall scupper, if applicable to the project.
🗌 Yes	□ N/A	i.	Show fixed seating for a ssembly occupancy to allow determination of occupancy posting required by <i>International Building Code</i> .
🗌 Yes	N/A	j.	Show wall sections with proposed material sizes, construction, and fire-rated assemblies.
🗌 Yes	N/A	k.	Show proposed plumbing fixtures and privacy screens on the plans.
🗌 Yes	🗌 N/A	I.	If masonry construction is proposed, include the following information:
			 Type of brick ties and spacing of weep holes Control joints Placement of wall flashing and reinforcement
Yes	□ N/A	m.	If appropriate for the proposed occupancy, plans should identify all hazardous material control areas, fire barriers, and the required fire-resistance ratings for these barriers. All identified control areas shall list the name, class, quantity and method of storage of all hazardous materials processed, manufactured or used in a man ufacturing process and contained within its fire ba rriers. Provide a Material Safety Data Sheet for each liste d hazardous material. See sections 414 and 415 of the <i>International Building Code</i> .
🗌 Yes	N/A	n.	Show the floor slab vapor barrier.
☐ Yes	□ N/A	0.	Show foundation waterproofing, if applicable.
☐ Yes	□ N/A	p.	All penetrations of fire-rated construction must be per manufacturer's details. The details shall meet or exceed the rating of construction being penetrated. The penetration details shall be exactly as tested by an approved testing laboratory or agency and shall include

☐ Yes ☐ Yes	□ N/A □ N/A	q. r.	their system numbers. New penetrations of existing fire-rated walls and assemblies shall be shown with appropriate designs. Show penthouse drawings. Provide on the drawings the calculations for the means of egress widths for the entire
			floor occupancy load and the existing capacity of all exits inclu ding all stairs, doors, corridors and ramped exits.
∐ Yes	□ N/A	S.	Show required ventilation louvers and vent sizes.
STRUC	TURAL PL	ANS	
☐ Yes	□ N/A	a.	Show foundation plans indicating the proposed slab elevations and type of found ation (i.e., mat foundation, caissons, spread footings, etc.)
	□ N/A	b.	Provide preliminary soil analysis data done by a licensed engineer, if required.
		C.	Indicate dimensions of foundations.
		d.	Show type, size and location of piling and pile caps for pile foundation.
		e.	Indicate grade beam sizes.
		f.	Indicate a footing schedule defining footing sizes and the required reinforcing.
∐ Yes	□ N/A	g.	Show the established footing depth below grade and method of frost protection allowed in section 1805.2.1 of the <i>International Building Code</i> .
_ Yes	□ N/A	h.	Indicate the thickness of the floor slab, size of reinforcing, slab elevations, and type and details of foundations.
🗌 Yes	🗌 N/A	i.	Indicate location, size, and amount of reinforcing steel.
🗌 Yes	🗌 N/A	j.	Show foundation corner reinforcing b ars and minimum overlapping (as applicable to project structure).
🗌 Yes	🗌 N/A	k.	Provide strength of concrete according to designed soil reports.
🗌 Yes	🗍 N/A	Ι.	Show beams, joists, girde rs, rafters, and/or truss layouts and details of connections, structural steel stud gage, gage size, and connections.
🗌 Yes	🗌 N/A	m.	Indicate the sizes and species of all wood members and their respective design strength.
☐ Yes	□ N/A	n.	Show all columns, girders, joists, purlins, beams, and base plates; for wood construction show all headers.
🗌 Yes	🗌 N/A	0.	
☐ Yes	□ N/A	р.	Indicate the type of anchoring for steel bearing directly on masonry.
☐ Yes	□ N/A	q.	Indicate design dead and live, wind, snow, seismic loads for floor areas, roofs, balconies,
	_	4.	porches, breezeways, corridors, stairs, mezzanines, and platforms. Show concentrated loads, i.e. file room s, machinery and forklift areas, if greater than those shown on the Code Summary Sheet. Identify shear walls, bracing, strapping, fastening, reinforcement and any special anchoring required.
∐ Yes	∐ N/A	r.	Where applicable, indicate on roof framing plan where concentrated loads (mechanical equipment, cranes, etc.) will be placed.
🗌 Yes	□ N/A	S.	Indicate on foundation and framing plans the location and lateral load re sisting system. (Show walls, braced frames, moment connections, etc.)
FIRE PR	OTECTIC	ON PL	ANS: 🗌 N/A
🗌 Yes	□ N/A	a.	Complete a sprinkler design data sheet and include it on the first plan of the sprinkler drawings.
🗌 Yes	□ N/A	b.	Show floor plans for each floor with sprinkler piping layout, pi pe sizes, pipe hanger details, piping materials, doors, walls and room identities.
			 Often, these shop drawings are not available at the time of initial plan submission. If this is the case, write in "NA," but note the following: These shop drawings must be submitted for review and approval at least two weeks before the projected installation date. Failure to obtain approval of the se drawings before installation could result not only in delay of the final insp ection and issuance of an occupancy permit, but also in rem oval and reconstruction of installations which f ail to
			meet UCC requirements.

🗌 Yes	□ N/A	C.	Show ceiling plans with sprinkler head(s) layout, walls, soffits, openi ngs, doors, dimensions and room identities.
☐ Yes	□ N/A	d.	Verify system design by providing hydraulic calculations along with the following: Recent water flow test 10 percent safety margin Type of backflow-preventer or reduced pressure zone showing equivalent foot loss Fire pump summary
🗌 Yes	□ N/A	e.	Note the type of sprinkler system used (e.g. 13, 13D, or 13R)
Yes	☐ N/A	f.	For residential occupancies such as apartments and condominiums, show sprinkler head locations at breezeways, if applicable.
☐ Yes	□ N/A	g.	Indicate the certified testing laboratory agency (e.g. U.L.), their test number and hourly ratings of all new and/or affected rated members and assemblies (i.e. columns, beams, floor/ceiling and ceiling/roof fire-rated design assemblies). Show all new and/or affected fire-rated walls with their ratings, if not show elsewhere.
☐ Yes	□ N/A	h.	All penetrations of fire-rated construction must be per manufacturer's details. Details shall meet or exceed ratings of construction being penetrated. Penetration details shall be exactly as tested by a certified testing laboratory or agency and shall i nclude their system numbers. All new penetrations of existing fire-rated walls and assemblies shall be shown with appropriate designs.
🗌 Yes	□ N/A	i.	Provide a fire alarm ri ser showing connection to a UL-app roved central station. Show tamper switcher on both OS and Y valves of backflow prevention device, unless shown elsewhere.
🗌 Yes	□ N/A	j.	Indicate commodity class (per section 2303 of the <i>International Fire Code</i>) and height of any storage.
🗌 Yes	🗌 N/A	k.	Provide Material Safety Data Sheet's for any hazardous materials (also specified under "Architectural Plans").
🗌 Yes	□ N/A	I.	Where special temperature-rated or high-temperature sprinklers are required, show sprinkler type(s) per area, office size, cut sheets with K-factor, water requirements, spray pattern, coverage and other pertinent data.

SYSTEM CALCULATIONS (FIRE PROTECTION):

Hydraulically calculated and pipe schedule fire systems should be designed with a 10 percent safety margin for all new buildings and additions to existing buildings. Calculations for hydraulic systems should include:

- Yes N/A a. Flow and pressure at each flowing sprinkler head
- Yes N/A b. Flow diagram for a grid system.

PLUMBING PLANS: N/A

🗌 Yes	□ N/A		 Show a site utilities plan, if not provided with the civil drawings. 1. Show the domestic water, fire, and irrigation services. 2. Show the location of water meters, backflow protection type and location. 3. Show the sanitary sewer service from building to public sewer or approved private
			sewage disposal system.
🗌 Yes	□ N/A	b.	Show interceptors as applicable to project and size by flow rate. (i.e. greas e, oil, lint, acid, sand)
🗌 Yes	□ N/A	C.	Provide plumbing plan layouts for each floor. These should show the water distribution and drain-waste-vent piping, and all details, notes, legends and schedules necessary to define the system being installed.
🗌 Yes	N/A	d	Show the location of all major components required for a complete system.
☐ Yes	□ N/A		Provide fixture and equipment schedule showing fixture number, detailed description, hot water, cold water, waste and vent connection sizes and other pertinent data.
🗌 Yes	□ N/A	f.	Identify all fixtures on floor plans and in riser diagrams with the plumbing fixture schedule number.
🗌 Yes	□ N/A	g.	Supply and Waste/Vent piping shall be shown on the floor plans. All pipe sizes shall be clearly shown. In congested areas (e.g. restaurants, grocery stores, etc.), isometrics are required.

🗌 Yes	□ N/A	h.	On buildings two stories and above, provide isometric diagrams and/or schematic riser diagrams for Supply and Waste/Vent piping and identify the risers by numb er (e.g. R1, R2, etc.). Show where all riser base terminations connect to the building drain, along with elliptic encoded for the diagram.
🗌 Yes	□ N/A	i.	with all interconnected piping on each floor plan. All pipe sizes shall be clearly defined. Show the water, sani tary drain-waste-vent piping and storm leaders/drains. Indi cate sizes and materials for above/below grade.
🗌 Yes	🗌 N/A	j.	Show slope of horizontal sanitary and storm drains that equal or exceed 3" diameter, if less than 1/8" per foot.
☐ Yes	□ N/A	k.	Indicate roof drains and emergen cy roof drains/scuppers with the areas they impact. Note that "emergency" = "secondary" = "overflow." See following roof drainage examples: Roof Drain – 6" RD (16880 SF) Emergency Roof Drain – 6" ERD (8180 SF) Parapet Wall Scupper – 8" x 5" WS (4000 SF) Emergency Scupper – 8" x 7" ES (4200 SF)
🗌 Yes	🗌 N/A	I.	Show toilet room layouts with minimum of $\frac{1}{4}$ " = 1 foot scale.
☐ Yes ☐ Yes	□ N/A □ N/A	m. n.	Show drinking fountain locations. All penetrations of fire-rated construction must be per manufacturer's details. The details shall meet or exceed ratin g of construction being penetrated. The penetration details shall be exactly as tested by an approved testing laboratory or agency and shall include their system numbers.
🗌 Yes	□ N/A	0.	Room names and numbers for each floor should be on a floor plan for each level.
☐ Yes ☐ Yes	□ N/A □ N/A	р. q.	
MECHA	NICAL PL	ANS	3: □ N/A
🗌 Yes	🗌 N/A	a.	Show all required wall louvers, penetrations and fans.
🗌 Yes	□ N/A	b.	Indicate roof-mounted equipment locations.
∐ Yes	□ N/A	C.	Show all mechanical equipment, piping, ductwork (above/below slab) on the mechanical
🗌 Yes	□ N/A	d.	floor and/or roof plan. Provide mechanical plans for each floor and the roof. These shall show the ductwork layouts, schedules, notes, legends, piping schematics, and details necessary to define the system being installed.
🗌 Yes	□ N/A	e.	Indicate air distribution devices and show cfm for all supply, return and exhaust devices.
	□ N/A	f.	Indicate the location of all equipment components required for a complete system.
		g.	Show the smoke ventilation of atriums and pressurization of high-rise stairwells.
		h.	Show condensation drains, primary and secondary, from the unit to the point of discharge.
		I. ;	Indicate toilet exhaust requirements.
🗌 Yes	□ N/A	j.	Show mechanical room layouts at sufficient scale for dimensions and details to be ascertained.
🗌 Yes	□ N/A	k.	Show the size of duct runs.
		к. I.	Indicate controls for fan shutdown: emergency manual and automatic smoke detection.
	□ N/A		Show the location of all UL 555-certified fire dampers, ceiling radiation dampers, smoke
🗌 Yes	□ N/A	n.	dampers, and fire doors. Show all fire-rated walls (both existing and new) with their ratin gs on the mechanical plans.
🗌 Yes	🗌 N/A	0.	
☐ Yes	□ N/A	p.	Room names and numbers for each floor should be on a floor plan for each level.
🗌 Yes	N/A	q.	Provide outside air ventilation rate per the International Mechanical Code.
Yes	☐ N/A	r.	Column line notations, if provided on the architectural/structural plans, shall be identified
🗌 Yes	□ N/A	S.	on the mechanical plans. Provide gas piping layout on the floor plan for each floor. If it is a m ulti-story building, all gas piping shall be shown per floor. In clude pipe sizes, water column, and type of material. Provide a sch edule of connected equipment, total BTUH dem and, total equivalent length, and most remote gas appliance.

ELECTRICAL PLANS: 🗌 N/A

🗌 Yes	□ N/A	a.	Provide panel schedules with circuit and feeder loading, overcurrent protection, and NEC load summaries for all new and/or affected panels and services (loading has to be evaluated by highest phase); include fault current data, short circuit ratings and fault
🗌 Yes	🗌 N/A	b.	current protection co-ordination. Provide a single line riser diagram showing all new and/or affected services, feeders, wire sizes and insulation types, and conduit sizes and types.
🗌 Yes	□ N/A	C.	Indicate number of services and their physical lo cations; clearly indicate m ains and characteristics.
🗌 Yes	□ N/A	d.	Indicate the grounding electrode conductor size with new and/or affected services and transformers; where necessary provide details or notes on methods.
🗌 Yes	□ N/A	e.	Show physical locations of all new and/or affected panels and switchgear (indicate front).
		f.	Indicate receptacle plans with circuitry.
		г. g.	Indicate lighting plans with circuitry.
		g. h.	Show electrical plans for each affected floor, including the roof.
		i.	Show wiring method(s), conduit sizes and types, termination temperature (60, 75, 90)
		1.	
	🗌 N/A	:	requirements, conductor sizes and insulation types.
∐ Yes		j.	Indicate the design and/or operation for a ny of the following applicable life safety
			systems: emergency generators, smoke evacuation, shaft p ressurization and relief,
			smoke detection, egress and emergency lighting, and fire alarms.
🗌 Yes	🗌 N/A	k.	Indicate how special needs such as classified (hazardous), corrosive and patient care are
			treated. Provide detailed plan of classified areas, the classifications and how complied
			with (i.e. han gers, waste treatment and collection, flammable dusts, gases or liquids,
—			spray booths, vehicle servicing and parking, etc.).
🗌 Yes	🗌 N/A	I.	Provide all HVAC nameplate data, including MCA and MOCP. List all oth er appliance
			and/or equipment (other than those which will be connected to a general use receptacle)
			with nameplate data (i.e. voltage, phasing, HP, KVA, FLA, RLA, etc.).
🗌 Yes	🗌 N/A	m.	Indicate all motor horsepower ratings, if not supplied elsewhere.
🗌 Yes	🗌 N/A	n.	Indicate the certified testing laboratory or agency (e.g. UL), their test # and hourly ratings
			of all new and/or affected rated members and assemblies (i.e. columns, beams,
			floor/ceiling, and ceiling/roof fire-rated design assemblies). Show all new and/or affected
			fire-rated walls with their ratings, if not shown elsewhere.
🗌 Yes	🗌 N/A	0.	All penetrations of fire-rated construction must be per manufacturer's details. The details
			shall meet or exceed ratings of construction being penetrated. Penetration details shall
			be exactly as tested by an approve d testing laboratory or agency and shall include their
			system numbers. New penetrations of existing fire-rated walls and assemblies shall be
			shown with appropriate designs.
🗌 Yes	N/A	p.	Provide all applicable International energy Conservation Code compliance data on the
		1-	Building Code Summary sheet or on the electrical plans.
🗌 Yes	🗌 N/A	q.	All submittals should include a listing and labeling statement. (All electrical materials,
		-	devices, appliances and equipment shall be la beled and li sted by a certif ied testing
			laboratory or agency.)

SPECIAL INSPECTIONS AND OBSERVATIONS STATEMENT Uniform Construction Code (UCC)

This statement must accompany permit applications for all construction for which special inspections and observations are required in the <i>International Building Code</i> .	on for which special g Code .
Project Name:	
Project Address:	
Owner: Tel	Telephone:

This is to certify that all the inspections and observations that I have checked on pages 2-3 and on page 4 of this statement are required for the project named above and will be performed by the designated individuals or firms. By signing this statement, I also acknowledge that:

- these inspections and observations must be performed by competent individuals in accordance with sections 1704 and 1709 (as applicable) and that the construction work must comply with the approved pla ns and specifications and all applicable provisions of the Uniform Construction Code;
- records of all required special inspections and testing observations (including any discrepancies and methods of correction of municipal UCC Officials, upon request; and, these discrepancies) will be retained and made available to
 - the Final Report section of this statement must be signed by me and a copy of this stat ement submitted to the municipal UCC inspector, at the time that the final inspection is performed and before a certificate of occupancy is issued.

Name of Design Professional in Responsible Charge

Signature of Design Professional in Responsible Charge

PA License Number Date signed (Month/Day/Year) PLEASE AFFIX SEAL IN SPACE TO THE LEFT.

CHECK EACH THAT APPLIES	TYPE OF SPECIAL INSPECTION OR OBSERVATION	NAME AND ADDRESS OF INDIVIDUAL AND/OR FIRM PERFORMING INSPECTION OR OBSERVATION	CREDENTIALS (Enter acronym from page 4. If "Other," please specify special training or basis for competency to perform work.)
	Inspection of Fabricators		
	Inspection of Steel Construction		
	Inspection of Concrete Construction		
	Inspection of Masonry Construction		
	Inspection of Wood Construction		
	Inspection of Soil Conditions		

CHECK EACH THAT APPLIES	TYPE OF SPECIAL INSPECTION OR OBSERVATION	NAME AND ADDRESS OF INDIVIDUAL AND/OR FIRM PERFORMING INSPECTION OR OBSERVATION	CREDENTIALS (Enter acronym from page 4. If "Other," please specify special training or basis for competency to perform work.)
	Inspection of Pile Foundations		
	Inspection of Pier Foundations		
	Inspection of Wood Panels and Veneers		
	Inspection of Sprayed Fire-Resistant Materials		
	Inspection of Smoke Control		
	Inspection of Exterior Insulation & Finish System (EIFS)		
	Structural Observations		

	Required Special Inspections or Observ	or Observations:		
FINAL REPORT	 Inspection of Fabricators Inspection of Steel Construction Inspection of Concrete Construction Inspection of Masonry Construction Inspection of Soil Conditions Structural Observations 	uction nstruction nstruction uction ns	 Inspection of Pile Foundations Inspection of Pier Foundations Inspection of Wood Panels and Veneers Inspection of Sprayed Fire-Resistant Materials Inspection of Smoke Controls Inspection of Exterior Insulation & Finish System (EIFS) 	
	I certify that I have reviewed the repolis in compliance with the approved pla	t on each of the inspect ans and specifications a	l certify that I have reviewed the report on each of the inspections or observations checked above. These reports indicate that the covered work is in compliance with the approved plans and specifications and all applicable provisions of the Uniform Construction Code.	
		S	Signature of Design Professional in Responsible Charge:	
			Date signed (Day/Month/Year):	
		I		
			American Concrete Institute Certified Concrete Field Testing Technician	
		AWS	American Welding Society Certified Welding Inspector	
		ASNT	American Society of Non-Destructive Testing	
		AWCI	Association of Wall and Ceiling Industries	
Ϋ́Ε	KEY for use in CREDENTIALS column:	MCA	Model code agency (ICC, BOCA, SBCCI, ICBO) special inspection certification	
	(on pages 2 and 3)	PA	Professional Architect (currently licensed)	
		PE	Professional Engineer (currently licensed)	[
		OTHER	Specialized training coursework or other basis for competency deemed acceptable	

Uniform Construction Code (UCC) ENERGY CODE PRESCRIPTIVE COMPLIANCE REPORT

PROJECT INFORMATION					
Project Name:		IECC Climate	ASHRAE/IESNA 90.1		
Street Number and Name:		Zone	Table		
City:	Zip Code:	Zone 4	□ B-13 □ B-14		
Political Subdivision:	County:	☐ Zone 6	☐ B-15 ☐ B-16 ☐ B-17		
PROJECT DESCRIPTION		· · · · ·	•		
Building floor area: sq	uare feet				
New construction Addition (conditioned) Alteration Unconditioned shell Unconditioned addition					
If using ASHRAE/IESNA 90.1 prescriptions, indicate if Semi-heated Space or if Cooled Space					
APPLICABLE STANDARDS					
Check which standards will be used for each component listed below.					
IECC CHAPTER 8 ASHRAE/IESNA 90.1 Building Envelope					
If no Building Envelope box was checked above, please indicate why the building envelope is exempt from the energy conservation requirements:					
Peak design rate of energy usage will be less than 3.4 Btu/h/sq. ft.					
Building or structure will be i	neither heated nor cooled.				
Attach either the IECC Chapter 8 or the ASHRAE/IESNA "Prescriptive Report" <u>for</u> <u>each of the components</u> checked above.					

IECC Prescri	ptive Report:	BUILDING	ENVELOPE

Window and Glazed Door Area/Above Grade Wall Area Ratio: ______ %

Skylights

Total Roof Area:	
Total Skylight Area:	
U-factor:	
Assembly Type:	

_____ square feet _____ square feet

R value of slab or below-grade walls:

Windows and Glass Doors (list individual assemblies):

Number/Location	PF	SHGC	U

Roof Assembly (list each type of assembly used):

Elements of Roof Assembly	Insulation Between Framing (R-Value)	Continuous Insulation (R-Value)

Floors Over Outdoor Air or Unconditioned Spaces (list each type of assembly used):

Elements Of Floor Assemblies	Insulation Between Framing (R-Value)	Continuous Insulation (R-Value)

Above-Grade Walls (list each type of assembly used):

Elements of Wall Assembly Used	No Framing (R-Value)	Metal Framing (R-Value)	Wood Framing (R-Value)

IECC BUILDING ENVELOPE CHECKLIST (requirements that will also be checked during inspection process):

- All joints and penetrations caulked, gasketed, weather-stripped, or otherwise sealed.
- Windows, doors, and skylights certified as meeting leakage requirements.
- All component R-values and U-factors labeled as certified.
- Stair, elevator shafts, vents and other dampers integral to building envelope are equipped with motorized dampers. (Gravity dampers may be used in buildings less than 3-stories in height.)
- Cargo/loading dock doors weather sealed.
- Recessed lighting fixtures installed per Section 802.3.7
- Vestibule provided at building entrances, with self-closing doors.
- Vapor retarder installed.

IECC Prescriptive Report: MECHANICAL SYSTEMS

Fill in all the requested information for either a simple or complex HVAC system.

Simple HVAC System & Equipment:

The section 803.2.1 design loads calculated per the ASHRAE Fundamentals Handbook are:

Heating Load = _____

Cooling Load =

803.2.2 HVAC Equipment Performance

Manufacturer Model Number	Capacity	Equipment Efficiency	Table used from Section 803	Required Efficiency

Complex HVAC Systems & Equipment:

The section 803.2.1 design loads calculated per the ASHRAE Fundamentals Handbook are:

Heating Load = _____ Cooling Load = _____

803.2.1 HVAC Equipment Performance

Manufacturer Model Number	Capacity	Equipment Efficiency	Table used from Section 803	Required Efficiency

Fill in all the information requested below for the service water heating system.

Section 804 Service Water Heating Equipment Performance

Manufacturer Model Number	Capacity	Equipment Efficiency	Equipment Type	Required Efficiency

IECC Building Mechanical Systems & Service Water Heater Requirement Checklist (requirements that will also be checked during inspection process):

- Load calculations per ASHRAE Fundamentals Handbook-2001.
- Plant Equipment and system capacity not greater than needed to meet loads.
- Minimum one temperature control device per zone.
- Stair and elevator shaft vents are equipped with motorized dampers
- Discharge dampers prohibited on constant volume fans & variable volume fans with motors >25hp.
- Balancing and pressure test connections on all hydronic terminal devices.
- Single-duct Variable Air Volume (VAV) terminals reduce primary air before reheating.
- Dual-duct (VAV) mixing boxes installed to minimize mixing.
- Controls capable of resetting supply air temperature (SAT) by 25% of SAT-room temperate difference.
- Minimum one humidity control device per installed humidification/dehumidification system.
- Automatic Controls: Setback to 55 degrees F (heat) & 85 degrees F (cool)
- Outside air supply and exhaust ducts equipped with gravity or motorized dampers with automatic shut off.
- Duct insulation: R-5 unconditioned spaces, R-8 outside building, R-8 between duct and exterior envelope.
- Duct construction per International Mechanical Code (IMC).
- Balancing devices provided in accordance with IMC.
- Minimum pipe insulation per Table 803.3.
- Heat traps in inlet/outlet fittings for service water heating.
- Pipe insulation for Service Water Heating per Section 804.5
- Water temperature controls: 110 degrees F for dwelling units, or 90 degrees F for other occupancies.
- Hydronic three-pipe systems not used.
- Operation and maintenance manual provided to building owner.

IECC Prescriptive Report: <u>Electrical Power & Lighting Systems</u>

Fill in all the requested information for either the entire building method or the tenant portion/portion of the building method.

Entire Building Method:

Building Use or Area Type from Table 805.5.2:	
Total Area of the Building (Sq. Ft.):	
Total Interior Light Power (Watts):	

Tenant Area or Portion of Building Method:

Tenant Area/ Building Portion	Use From Table 805.5.2	Total Area sq.ft.	Total Interior Lighting Power (Watts)

IECC Electrical Power & Lighting Systems Requirements Checklist <u>requirements that will also be checked</u> <u>during inspection process</u>):

- Exterior Lighting: Efficacy greater than 45 lumens/W
- Independent controls for each space (switch/occupancy sensor).
- Master switch at entry to hotel/motel guest rooms.
- Individual dwelling units separately metered.
- Each space provided with a manual control to provide uniform light reduction capability.
- If area is corridor, storeroom, restroom, or lobby; area must be continuously illuminated; areas greater than 250 sq. ft. or use less than 0.6 watts/sq. ft.
- Photocell/astronomical time switch on exterior lighting.
- Tandem wired one-lamp & 3-lamp ballasted luminaries.

ASHRAE/IESNA 90.1 Prescriptive Report: Electrical Power & Lighting Systems

Fill in all the requested information for either the entire building method or the tenant portion/portion of the building method.

Entire Building Method:

Building Use or Area Type from Table 9.3.1.1: Total Area of the Building (Sq.Ft.): Total Interior Light Power (Watts):

Tenant Area or Portion of Building Method:

Tenant Area/ Building Portion	Use From Table 9.3.1.2	Total Area Sq. Ft.	Total Interior Lighting Power (Watts)

ASHRAE/IESNA 90.1 Electric Power & Lighting Requirements Checklist (requirements that will also be checked during inspection process):

- Minimum Efficacy of 60 lumens/watts for lamps greater than 100W used for exterior lighting.
- Lighting power for freestanding canopy areas for building entrances with canopies less than or equal to 3 watts per square foot.
- Lighting power for building entrances without a canopy less than or equal to 33 watts per linear foot of exterior door width.
- Lighting power for buildings exits less than or equal to 20 watts per linear foot of exit door width.
- Lighting power for building facades less than or equal to 0.25 watts per square foot of the illuminated area.
- Independent manual or occupancy sensing controls for each space (remote switch with indicator allowed for safety or security).
- Automatic shutoff control for lighting in > 5000 sq.ft. buildings by time-of-day device, occupant sensor or other automatic control.
- Master switch at entry to hotel/motel guest room.
- Photocell/astronomical time switch on exterior lights (except areas requiring lighting during daylight hours).
- Tandem wired one-lamp and three-lamp ballasted luminaries (except high-frequency ballasts; luminaries not on same switch).
- Feeder conductors have been designed for a maximum voltage drop of 2 percent.
- Branch circuit conductors have been designed for a maximum voltage drop of 3 percent.

ASHRAE/IESNA 90.1 Prescriptive Report: Building Envelope

Roof Assembly (list each type of assembly used per table 5.3)

Envelope Option: Non-residential	Semi-heated	Opaque Elements	Assembly Max. U	Insulation Min. R

Walls, Above-Grade (list each type of assembly used per table 5.3)

Max. U	Min. R

Floor Assembly (list each type of assembly used per table 5.3)

List Building Envelope Option: Residential Non-residential Semi-hea	ated	Opaque Elements	Assembly Max. U	Insulation Min. R

Slab on Grade Floors (list each type of assembly used per table 5.3)

List Building Envelope Option:	Opaque Elements	Assembly	Insulation
Residential Non-residential Semi-heated		Max. U	Min. R

Wall, Below Grade (list each type of assembly used per table 5.3)

Envelope Option: Non-residential	Semi-heated	Opaque Elements	Assembly Max. U

Opaque Doors (list each type of assembly used per table 5.3)

List Building Envelope Option: Residential Non-residential Semi-heated	Opaque Elements	Assembly Max. U

ASHRAE/IESNA 90.1 Prescriptive Report: <u>Building Envelope</u> (Continued)

renestration (list each type of assembly used per table 3.3)					
List Building Envelope Option:	% Vertical	SHGC	Assembly	SHGC	SHGC
Residential Non-residential Semi-heated	Glazing	Multiplier	Max. U	North	All

Fenestration (list each type of assembly used per table 5.3)

Skylights (list each type of assembly used per table 5.3)

List Building Envelope Option: Residential Non-residential Semi-heated	Туре	% of Roof	Assembly Max.	SHGC Max.

ASHRAE/IESNA 90.1 Building Envelope Requirements Checklist (requirements that will also be checked during inspection process):

- Open-blown or poured loose-fill insulation has not been used in attic roof spaces with ceiling slope greater than 3 in 12.
- Wherever vents occur, vents are baffled to deflect incoming air above the insulation.
- Recessed lights, equipment and ducts are not affecting insulation thickness.
- No roof insulation is installed on a suspended ceiling with removable ceiling panels.
- All exterior insulation is covered with protective material.
- Cargo and loading dock doors are equipped with weather seals.
- Windows & skylights are labeled & certified by the manufactures for U-factor & SHGC.
- Fixed windows & skylights unlabeled by manufacturer have been site labeled using the default U-factor & SHGC.
- Other unlabeled vertical fenestration, operable and fixed, not labeled by the manufacturer, has been site labeled using the default U-factor and SHGC.
- All joints & penetrations are caulked, gasketed, weather-stripped, or otherwise sealed.
- Windows, doors, and skylights certified as meeting leakage requirements.
- Components R-values & U-factors labeled as certified.
- Building entrance doors have a vestibule and equipped with closing devices.

ASHRAE/IESNA 90.1 Prescriptive Report: Mechanical Systems (Simple)

A building that is <u>less than 2 stories in height</u>, and, <u>has less than 25,000 total square feet floor area</u>, and, <u>has a single HVAC zone</u>, must meet the requirements for a simple mechanical system.

If the requirements for a **simple mechanical system** apply, fill in all of the following information.

Cooling (if provided)				
Manufacturer Name				
Mfg'er Specified Efficiency				
	Air Conditioner Min. Efficiency (Table 6.2.1A)			
	Heat Pump Min. Efficiency (Table 6.2.1B)			
□ P	ackaged Terminal & Room AC & Heat Pump Min. Efficiency (Table 6.2.1D)			
	Is Economizer required per Table 6.1.3?			
Heating				
Manufacturer Name				
Mfg'er Specified Efficiency				
	Heat Pump Min. Efficiency (Table 6.2.1A)			
	Heat Pump Min. Efficiency (Table 6.2.1D)			
	Fuel Fired Furnace Min. Efficiency (Table 6.2.1E)			
	Fuel Fired Boiler Min. Efficiency (Table 6.2.1F)			
	lectric Resistance Heat			
Service Hot Water				
Manufacturer Name				
Mfg'er Specified Efficiency				
	Load calculated per 7.2.1			
	Efficiency/Performance Requirements per 7.2.2			
	Prescriptive Path pe r 7.3, if <u>combined</u>			
	boiler/service hot water			

ASHRAE/IESNA 90.1 Mechanical Systems (Simplified) Requirements Checklist (requirements that will also be checked during inspection process):

- Energy recovery ventilation required if outside air quality supplied by the system is greater than 3000 cfm & greater than 70% of the supply air quantity at min. outside air designs.
- Manual change over or dual set-point thermostat supplied.
- Heat pump controls to prevent supplemental heater operation.
- Systems controls to prevent reheat or any other form of simultaneous heating & cooling for humidity control supplied.
- Programmable time clock on HVAC systems greater than 15,000 BTU/H & supply fan greater than 3/4/hp.
- HVAC piping shall be insulated in accordance with Table 6.2.4.1.3 insulation suitable for outdoor service.
- Ductwork & plenums insulated in accordance with Table 6.2.4.1.2A & 6.2.4.1.2B and ducted systems air balanced.
- Thermostats shall be interconnected to prevent simultaneous heating & cooling.

ASHRAE/IESNA 90.1 Mechanical Systems (Simple) Requirements Checklist (continued)

- Dampers automatically shut on systems greater than 300 cfm.
- Optimum start controls supplied on systems with capacities greater than 10,000 cfm.

ASHRAE/IESNA 90.1 Service Hot Water Systems Requirements Checklist (requirements that will also be checked during inspection process):

- Service Hot Water Piping Insulation meets 7.2.3
- Temperature maintenance automatic time switches installed (7.2.4.2)
- Outlet temperature controls installed (7.2.4.4)
- Circulating pump controls installed (7.2.4.4)
- Storage temperature controls installed (7.2.4.1)
- Heat traps installed (7.2.6)

ASHRAE/IESNA 90.1 Prescriptive Report: Mechanical Systems (Complex)

If the requirements for a **complex mechanical system** apply, fill in all of the following information.

Heating System Design Load: _____ Cooling System Design Load: _____

HVAC Equipment Performance per section 6.2.1

Manufacturer/ Model #	Capacity	Equipment Efficiency	Table used from Section 6.2.1	Required Efficiency	1992 Epact

Service Hot Water		
Manufacturer Name		
Mfg'er Specified Efficiency		
	Load calculated per 7.2.1	
	Efficiency/Performance Requirements per 7.2.2	
	Prescriptive Path pe r 7.3, if <u>combined</u>	
	boiler/service hot water	

ASHRAE/IESNA 90.1 Mechanical Systems (Complex) Requirements Checklist (requirements that will also be checked during inspection process):

- Economizers per 6.3.1
- Simultaneous heating & cooling limitations per 6.3.2
- Air system design & condoles per 6.3.3
- Hydronic system design & control 6.3.2.2.3
- Heat rejection equipment per 6.3.5
- Energy recovery per 6.3.6.
- Exhaust Hoods per 6.3.7
- Radiant Heating systems per 6.3.8
- Hot gas bypass limitations per 6.3.9
- Service hot water piping insulation meets 7.2.3
- Temperature maintenance automatic time switches installed per 7.2.4.2
- Outlet temperature controls installed per 7.2.4.3
- Circulating pump controls installed per 7.2.4.4
- Storage temperature controls installed per 7.2.4.1
- Heat traps installed per 7.2.6